

ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO.: DLC20

NAME: Griffith Tiered Chandelier

MATERIAL TYPE: Steel

FINISH: Bronze


SOCKET TYPE: E12

SOCKET QTY: 9

BULB WATTAGE: 60 W/13W CFL/8W LED

VOLTAGE: 110-120 V

ITEM NET WEIGHT: 21.8 LBS



PARTS INCLUDED:

Mounting Plate (A)	Qty: 1 Pc	Lamp Rod (G)	Qty: 1 Pc
Canopy (B)	Qty: 1 Pc	Lamp Body (I)	Qty: 1 Pc
Collar Loop (C)	Qty: 1 Pc	Socket (N)	Qty: 9 Pcs
Rods (D)	Qty: 4 Pcs		
Hex Screws (E)	Qty: 12 Pcs		
Lamp Body (F)	Qty: 1 Pc		

HARDWARE INCLUDED:

Mounting Screws (J)	Qty: 2 Pcs
Plastic Wire Connector (K)	Qty: 3 Pcs
Allen Wrench (U)	Qty: 1 Pc

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.



TO ASSEMBLE:

1. Shut off the main electrical supply from the main fuse box/circuit breaker.
2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
3. Gently pull wiring down from ceiling junction box and allow to hang.
4. Connect lamp body (F) and lamp body (I) by lamp rod (G) first, then connect canopy (B) with rod (D1, D2, D3, D4), when you connect the rods, loosen the small hex screws (E) first then tighten with Allen wrench (L) after all rods are connected. be sure all the hex screws (E) are tight enough.
5. Carefully inspect the pendant's fixture wires. Neutral fixture wire: White. Hot fixture wire: Black. Ground wire: Green
6. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
7. Attach the neutral fixture wire from the pendant to the neutral junction box wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
8. Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape. DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
9. Gently tuck the wire connections neatly into the ceiling junction box.
10. Place the mounting plate (A) over the center of the ceiling junction box.
11. Align holes in mounting plate (A) with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
12. push canopy (B) up over the mounting plate (A) until it is flush with the ceiling.
13. Push collar loop (C) through hole in canopy (B) and thread onto nipple on the mounting plate (A). Secure by turning collar loop (C) clockwise until canopy (B) is flush with the ceiling.
14. Insert 9 TYPE-B 60W or/cfl 13w or /led 8w bulb (not included) into socket (N). DO NOT EXCEED SPECIFIED WATTAGE OF CHANDELIER.
15. Restore power to junction box and test fixture.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.