

ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO.: DLI13 NAME: Morgan Flush Mount

MATERIAL TYPE: Brass FINISH: Vintage Brass

SOCKET TYPE: E12 SOCKET QTY: 8

BULB WATTAGE: 25W Bulb/7W SBCFL/5W SBLED

VOLTAGE: 110-120 V ITEM NET WEIGHT: 25.50 lbs

PARTS INCLUDED:

Mounting Plate	Qty: 1 Pc	Qty:
Canopy	Qty: 1 Pc	Qty:
Loop	Qty: 1 Pc	Qty:
Socket Assembly	Qty: 1 Pc	Qty:
Hanging Pipe	Qty: 5 Pcs (1) 4" , (1) 3" , (1) 6" ,(2) 12"	

HARDWARE INCLUDED:

Mounting Screws	2	Hexangular Screw 8 Pcs	
Plastic Wire Connector	2	Allen Wrench	1 Pc
Green Ground Screw	1		

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.

For customer service questions call 1-800-338-2150



TO ASSEMBLE:

1. Shut off the main electrical supply from the main fuse box/circuit breaker.
2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
3. Gently pull wiring down from ceiling junction box and allow to hang.
4. Remove mounting plate from the canopy by unscrewing the collar.
5. Carefully inspect the pendant's fixture wires.
Neutral fixture wire: White
Hot fixture wire: Black
Ground wire: Green
6. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire nut and wrap the connection with electrical tape.
7. Attach the neutral fixture wire from the pendant to the neutral junctionbox wire (usually white). Fasten each together with a wire nut and wrap the connection with electrical tape.
8. Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape.
DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
9. Gently tuck the wire connections neatly into the ceiling junction box.
10. Place the mounting plate over the center of the ceiling junction box.
11. Align holes in mounting plate with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
12. Push canopy up over the mounting plate until it is flush with the ceiling.
13. Push collar through hole in canopy and thread onto nipple on the mounting plate. Secure by turning collar clockwise until canopy is flush with the ceiling.
14. Insert (8) **Type B 25W Bulb/7W SBCFL/5W SBLED** bulb into fixture. DO NOT EXCEED SPECIFIED WATTAGE.
14. Restore power to junction box and test fixture.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

A R T E R I O R S