


ASSEMBLY INSTRUCTIONS

ITEM DESCRIPTION:

ITEM NO.: DPC25	NAME: MELODY PENDANT
MATERIAL TYPE: IRON, MARBLE, GLASS	FINISH: CHATTERED ANTIQUE BRASS
SOCKET TYPE: E12	SOCKET QTY: 1
BULB WATTAGE: 40W or /9W CFL or/4W LED	
VOLTAGE: 110V-120V	ITEM NET WEIGHT: 12LBS



PARTS INCLUDED:

Mounting Plate (A)	Qty: 1Pc	Wire clamp (G)	Qty: 1Pc
Canopy (B)	Qty: 1Pc	Electric wire (H)	Qty: 1Pc
Collar Loop (C)	Qty: 1Pc	steel wire (I)	Qty: 1Pc
Socket (D)	Qty: 1Pc	Connector (L)	Qty: 1Pc
Glass Shade (F)	Qty: 1Pc	Metal Cap (M)	Qty: 1Pc

HARDWARE INCLUDED:

Mounting Screws	Qty : 2Pcs	Canopy Screws
Plastic Wire Connector(K)	Qty : 3Pcs	
Green Ground Screw	Qty : 1Pc	

TO INSTALL YOU WILL NEED:

- 2 people recommended
- Phillips Screwdriver

These instructions are provided for safety. It is very important that they are read carefully and completely before beginning installation.

We strongly suggest that all hard-wired fixtures must be installed by a professional electrician.

For customer service questions call 1-800-338-2150



TO ASSEMBLE:

1. Shut off the main electrical supply from the main fuse box/circuit breaker.
2. Carefully unpack all fixture parts and hardware and lay them on a soft surface for assembly.
3. Gently pull wiring down from ceiling junction box and allow to hang.
4. Remove mounting plate (A) from the Connector (L) turning in a counterclockwise direction.
5. **Carefully inspect the pendant's fixture wires. Neutral fixture wire: White Hot fixture wire: Black Ground wire: Green**
6. Wrap ground wire of lamp assembly and ground wire of junction box together and fasten together with a wire connector(K) and wrap the connection with electrical tape.
7. Attach the neutral fixture wire from the pendant to the neutral junction box wire (usually white). Fasten each together with a connector(K) and wrap the connection with electrical tape.
8. Attach the hot fixture wire from the pendant to the hot junction box wire (usually black). Fasten each together with a wire nut and wrap the connection with electrical tape. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.**
9. Gently tuck the wire connections neatly into the ceiling junction box.
10. Place the mounting plate(A) over the center of the ceiling junction box.
11. Align holes in mounting plate(A) with holes in junction box and attach with two mounting bolts. Secure bolts with a Phillips head screwdriver.
12. Hold the wire clamp (G) with one hand, and pull the steel wire rope with the other hand. Once you reach the desired length, remove your hand from the wire clamp(G).
13. Push canopy (B) up over the mounting plate(A) until it is flush with the ceiling.
14. Push collar loop (C) to connect with connector (L) by turning in a clockwise direction until canopy(B) is flush with the ceiling.
15. Insert 1 TYPE-G 40W or /9W CFL or/4W LED bulb(not included) into socket(D). **DO NOT EXCEED SPECIFIED WATTAGE OF PENDANT.**
16. Put and assemble the glass shade (F) with the metal cap(M) carefully by rotating in a clockwise direction.
17. Restore power to junction box and test fixture.

CARE INSTRUCTIONS:

Wipe with a soft, dry cloth. To protect finish, avoid the use of chemicals and household cleaners.

ARTERIO RS